

INITIAL	START	RUN-UP	TAKEOFF	DESCENT	AFTER LANDING
Weather & Den. Alt. Weight & Balance Performance Req. Flight Plan - File Papers - A.R.O.W. Fuel - Both Control Lock Master - On Flaps - Extend Pitot Heat - Test Lights - Int. / Ext. Fuel Gauges - True Master - Off EXTERIOR SUMMARY After Geographical Check Fuel Quantity Fuel Quality Caps/Drains/Vents Engine / Oil / Belt Prop / Air Intake Exhaust System Stall Indicator - Test Surfaces & Controls Pitot & Static Ports Gear / Tires / Brakes Antennas Ties / Chocks Baggage Door Final Walk Around INTERIOR Passenger Brief Hobbs / Tach Time Circuit Breakers Alternate Static Brakes - Pedal Test	Seat Track/Back-Lock Avionics - Off Autopilot - Off Carb Heat - Off Beacon - On Mixture - Full Rich Throttle - Slight Prime Brakes Prop - Clear Master - On Mags - Start Oil Pressure Lights - As Req. Mixture - As Req. PRE-TAXI / TAXI Seat Belts / Harness Flaps - Up Heat / Vent / Defrost Avionics - On / Set Transpond - STBY ATIS / AWOS Altimeter - Set Radio - Test Taxi Light - As Req. Brakes - Test Attitude Indic. - Test Turn Coord. - Test H.I./Compass - Test	Brakes - Set Fuel - Both Trim - Takeoff Flight Controls Instruments Mixture - Best Power Primer - In & Lock 1700 RPM Mags (R & L) - Test Carb Heat - Test Vacuum Amps / Volts Oil Pressure Oil Temperature Idle - Check Closed Throttle Friction PRE-TAKEOFF Flaps - 0°- 10° Mixture - Best Power Carb Heat - Off <i>Or As Req</i> H.I. To Compass Doors / Windows Transp - Alt + Sqwk Landing Light - On Strobes - As Req. Time - Note Brakes - Release <i>Abort Plan - Ready!</i>	Full Throttle 2300 RPM (Min) Oil Pressure Rotate * 55 (63) Vy - 78 (90) Flaps - Up CLIMB 70-78 (80-90) Power Mixture Instruments Taxi / Land Light - Off Flight Plan - Open CRUISE Power Mixture Instruments H.I. To Compass	Mixture - Richen Fuel - Both Carb Heat - As Req. ATIS / AWOS Altimeter - Set Instruments H.I. To Compass PRE-LANDING Landing Light - On Autopilot - Off Seat Belt / Harness Mixture - Best Power Carb Heat - On Fuel - Both Flaps - As Req. LANDING Flaps - 40° <i>Or As Req.</i> Speed * 60 (69) G.U.M.P.F.S. GO AROUND Power - Full Carb Heat - Off Positive Rate Climb Flaps - Retract Slowly	Flaps - Up Carb Heat - Off Strobes - Off Landing Light - Off Taxi Light - As Req. Pitot Heat - Off Trim - Takeoff Transpond - STBY SECURING ELT - Verify Silent Avionics - Off Mixture - Full Lean Mags - Off Master - Off Fuel - Left or Right Lights - Off Hobbs / Tach Time Control Lock Chocks Tie Downs Pitot Cover Baggage Door Cabin Doors Close Flight Plan * Adjust Speed As Needed For Conditions

X Wind • Max Demo'd - 15 (17)	Vs0 • Stall with flaps - 41 (47)	Best Glide (1976) (2000 lbs) - 61 (70)	Vno • Max Struct. Cruise - 128 (147)
Vr • Rotation Speed - 55 (63)	Vs • Stall without flaps - 47 (54)	Best Glide (1976) (Full Gross) - 65 (75)	Vfe • Flaps Extended - 85 (98)
Vx • Best Angle Climb - 64 (74)	Best Glide (2000 lbs) - 65 (75)	Va • Max Abrupt Ctr (2000 lbs) - 90 (104)	Vne • Never Exceed - 160 (184)
Vy • Best Rate Climb - 78 (90)	Best Glide (Full Gross) - 70 (80)	Va • Max Abrupt (Full Gross) - 97 (112)	

	KNOTS (MPH)	FLAPS °	- NOTES -
DEPARTURE			172M - Speeds May Vary Slightly Depending On Year (IAS & CAS) Short Field w/Obstacle: 0° Flaps. Climb 59 (68) Until Clear. Short w/o Obstacle or Soft Field: 10° Flaps.
Rotation *	55 (63)	0	
Best Angle Climb	64 (74)	0	
Best Rate Climb	78 (90)	0	
CRUISE (IAS - 5,000')			
Economy	99 (114)	0	2300 RPM - 6.4 GPH - 54%
Normal	108 (124)	0	2450 RPM - 7.1 GPH - 63%
Maximum	117 (135)	0	2625 RPM - 8.3 GPH - 75%
ARRIVAL			
Approach	70 (81)	10-20	1700 RPM (Initially)
Short Final *	60 (69)	30-40	Idle - 1200 RPM

WARNING: Permission to use this CheckMate® is granted to the authorized purchaser only. No warranties, either express or implied, of any kind, are made hereunder, including, but not limited to any warranties for fitness for particular use. The information herein varies according to individual aircraft and model year. This information constitutes only partial information necessary to properly operate an aircraft and is not to be used as a substitute for the original manufacturer's aircraft manual. Purchaser assumes all risk of use in using this product. Purchaser consents that CheckMate Aviation Inc., or any related entity, bears no liability for the use of this product.

Specs Are In: LBS, KIAS, Sea Level, Standard Day, Normal Category, Max Gross Wt., No Wind, "Best Power", Wheel Pants, New Engine. () = MPH.
 © ALL RIGHTS RESERVED (Ver 7.61)
 CheckMate Aviation Inc. 1992-2004, 800-359-3741

POWER LOSS IMMEDIATELY AFTER TAKEOFF / NO RESTART

MAINTAIN AIRCRAFT CONTROL
 BEST GLIDE – **70 KIAS** (80 MPH) (Full Gross Weight)
 BEST GLIDE (1976) – **65 KIAS** (75 MPH) (Full Gross Weight)
 FUEL SELECTOR – OFF
 MIXTURE – FULL LEAN / IDLE CUTOFF
 FLAPS – DOWN
 MASTER & MAGS – OFF (Unlatch Doors)

POWER LOSS IN FLIGHT

BEST GLIDE – **70 KIAS** (80 MPH) (Full Gross Weight)
 BEST GLIDE (1976) – **65 KIAS** (75 MPH) (Full Gross Weight)
 CARB HEAT – ON (Also Supplies Alternate Air)
 NOTE WIND DIRECTION & VELOCITY
 PICK LANDING SITE & INITIATE APPROACH
 FUEL SELECTOR – CHECK / SWITCH / BOTH (Note Gauges)
 MIXTURE – FULL RICH
 FUEL PRIMER – LOCKED (Try Re-Priming)
 MAGNETOS – CHECK ALL
 MASTER – ON

IF NO RESTART & TIME PERMITS

MAINTAIN BEST GLIDE
 SQUAWK 7700
 DECLARE EMERGENCY (TWR, APP, Unicom, 121.5)
 FUEL SELECTOR – OFF
 MIXTURE – FULL LEAN / IDLE CUTOFF
 SEATBELTS / HARNESS
 FLAPS – AS NEEDED (Full Flaps When Field Assured)
 MASTER & MAGS – OFF
 UNLATCH DOORS
 PROTECT BODY

ELECTRICAL FIRE IN FLIGHT

ALL ELECTRICAL DEVICES + MASTER – OFF (Mags On)
 CLOSE VENTS, CABIN HEAT, & AIR
 IF FIRE OUT – MASTER ON ONLY IF CRITICAL (Vents – Open)
 THEN ONE ESSENTIAL ELECTRICAL DEVICE AT A TIME
 RESET CIRCUIT BREAKER(S) ONLY IF CRITICAL – LAND ASAP

ENGINE FIRE IN FLIGHT

MIXTURE – FULL LEAN / IDLE CUTOFF
 FUEL SELECTOR – OFF
 MASTER SWITCH – OFF
 CABIN HEAT & AIR – OFF (Except Overhead Vents)
 INCREASE AIRSPEED TO EXTINGUISH – LAND ASAP

ENGINE FIRE DURING START

CONTINUE CRANKING ENGINE
 IF START – RUN A FEW SECONDS - SHUTDOWN - INSPECT
 IF NO START – IDLE MIXTURE CUTOFF & FUEL SELECTOR OFF
 THROTTLE FULL OPEN
 CONTINUE CRANKING ENGINE A FEW SECONDS
 MASTER & MAGS – OFF
 EVACUATE / FIRE EXTINGUISHER

ICING

PITOT HEAT – ON
 CARB HEAT – ON OR AS REQUIRED
 CABIN HEAT & DEFROST – MAXIMUM
 STRONGLY CONSIDER 180° TURN
 ATTAIN HIGHER OR LOWER ALTITUDE
 INCREASE ENGINE SPEED
 FLAPS – NOT RECOMMENDED FOR LANDING
 LAND FASTER AS NEEDED

OTHER

EXCESSIVE RATE OF CHARGE: Over Voltage Warning Light Will illuminate if reaches approx. 16 Volts. To Reactivate, Turn Both Sides Of The Master Switch Off / Then On Again. If Light Comes On Again, Terminate Flight A.S.A.P.

INSUFFICIENT RATE OF CHARGE: Nonessential Electric – Off / Terminate Flight A.S.A.P.

RADIO OUT: Check Circuit Breakers & VOLUME
 Recycle Alternator Switch
 If IFR & Still Out, Set Transponder At 7600.
 (Suggested For VFR If In B, C, D Airspace)

UNICOM: 122.7 – 122.8 – 122.95 – 123.0 – 123.05
 MULTICOM: 122.9 (CTAF), 122.75, 122.85 (Air To Air)
 FLIGHT WATCH: 122.0

TOWER SIGNALS	ON GROUND	IN FLIGHT
Steady Green	Cleared For Takeoff	Cleared To Land
Flashing Green	Cleared To Taxi	Return For Landing
Steady Red	Stop	Yield & Continue Circling
Flashing Red	Tail Clear of Landing Area	Airport Unsafe – Do Not Land
Flashing White	Return To Starting Point	N/A
Alternating Red & Green	Use Extreme Caution	Use Extreme Caution

* Every Plane Has A Different Empty Weight And Useful Load
 Cessna 172 M (Lycoming: O-320-E2D, 150HP)

* Empty Weight: LBS (Specific Plane Weight)
 * Max. Useful Load: LBS (Including Fuel @ 6 lbs/gal)
 Max. Baggage Area: 120 LBS (Included In Useful Load)
 Max. T.O. Weight: 2300 LBS

Fuel Type: 100LL (Blue) / 100 (Green) / 80 (Red)
 Usable Fuel: 38 Gallons (48 L.R Tanks)
 Oil Capacity: 8 Quarts (Minimum 6)
 Electrical: 12-14 VOLT / 60 AMP
 Tire Pressure: Nose-31 PSI / Main - 29 PSI (5.00 x 5)
 Tire Pressure: Nose-26 PSI / Main - 29 PSI (6.00 x 6)